



MOTOR DATA SHEET

MOTOR PART CODE:

160.063TECCB3-IE2

FRAME SIZE:

355M1-6

50Hz

Output (kW)	160
Rotation Speed (rpm)	980
Voltage	400/690
Full Load Current (A)	286.6/165.46
Full Load Torque (Nm)	1559.2

60Hz

Output (kW)	192
Rotation Speed (rpm)	1176
Voltage	480/828
Full Load Current (A)	286.6/165.46
Full Load Torque (Nm)	1299.33

Efficiency Data

100%	75%	50%
94.8	94.9	92.5

Factory Reference	T2C 355M1-6
Tst/Tn (times)	2
Tmax/Tn	2.3
Noise (dB)	92
Moment of inertia	8.97637
Type of feet	Fixed feet
Protection	IP55
Rotation Direction	F / R
Cable Glands	2 - M63× 1.5
Paint Colour	RAL 7024
Efficiency	IE2
Bearing (DE)	NU322 C3



Power Factor (cos)	0.85
Tmin/Tn	1.3
Ist/In (Times)	6.5
Net Weight (Kg)	1537
Housing material	Cast Iron
Insulation Class	F
Thermal Protection	PTC 140°C
Duty Cycle	S1
Cooling	IC 411
Ambient Temperature	-20°C to +40°C
Bearing Brand	NSK
Bearing (NDE)	6322 C3

Motors designed and manufactured in accordance with:

**IEC 60034
IEC 60038
IEC 60072
2014/30/EU (EMC)
2014/35/EU (LVD)
2011/65/EU (RoHS 2)**

www.tecmotors.co.uk

TEC Electric Motors Ltd. reserves the right to amend or change motor designs or data sheet information



TYPE	D	E	F	G	DH	ED	L	
Y2-355M/L-2P	Ø75	140	20 _{-0.043}	68	M20x42	110	1500	
Y2-355M/L-4/6/8P	Ø100	210	28 _{-0.052}	90	M24x50	160	1570	

Drawn By	Date	TC 355ML4 B3
A442313	27/11/2017	
Approved by	Date	
L. Overton	27/11/2017	
Issue No =	Date	 www.tecmotors.co.uk
BM01/A001	27/11/2017	