



MOTOR DATA SHEET

MOTOR PART CODE:

22.043TECAB3-IE2

FRAME SIZE:

180L-4

50Hz

Output (kW)	22
Rotation Speed (rpm)	1460
Voltage	400/690
Full Load Current (A)	39.39 22.74
Full Load Torque (Nm)	143.9041096

60Hz

Output (kW)	26.4
Rotation Speed (rpm)	1752
Voltage	480 828
Full Load Current (A)	39.39 22.74
Full Load Torque (Nm)	119.92

Efficiency Data

100%	75%	50%
91.6	92.2	91.9

Factory Reference	MS2 180L-4
Tst/Tn (times)	2.4
Tmax/Tn	2.8
Noise (dB)	80
Moment of inertia	0.1732931
Type of feet	Removable feet
Protection	IP55
Rotation Direction	F / R
Cable Glands	2 - M32× 1.5
Paint Colour	RAL 7024
Efficiency	IE2
Bearing (DE)	6311 2RS C3




Power Factor (cos)	0.88
Tmin/Tn	1.7
Ist/In (Times)	7.7
Net Weight (Kg)	129
Housing material	Aluminum
Insulation Class	F
Thermal Protection	PTC 130°C
Duty Cycle	S1
Cooling	IC411
Ambient Temperature	-20°C to + 40°C
Bearing Brand	NSK
Bearing (NDE)	6211 2RS C3

Motors designed and manufactured in accordance with:

**IEC 60034
IEC 60038
IEC 60072
2014/30/EU (EMC)
2014/35/EU (LVD)
2011/65/EU (RoHS 2)**

www.tecmotors.co.uk

TEC Electric Motors Ltd. reserves the right to amend or change motor designs or data sheet information



Drawn By	Date
TECHTOP	27/11/2017
Approved by	Date
L. Overton	27/11/2017
Issue No =	Date
001/A	27/11/2017

TECA 180 B3



www.tecmotors.co.uk