


GEARS & RACKS

Imperial Spur Gears

Imperial Spur Gears in Steel 24DP, 20° P.A



- Intermediate sizes and special gears to drawing up to 39" diameter
- Standard tolerances, unless otherwise stated ± 0.010 ins
- Standard: BS 436 Pt1, fig 1. Grade 8 / 9
- All dimensions in inches
- Steel EN8, (080M40/080M46) or equivalent

Code	No. teeth	Pitch Ø dp	Outside Ø de	Hub/Boss Ø dm	Bore Ø H8	O/A width A	Face width B
SSDP24/15B	15	0.625	0.708	0.484	0.3125	0.625	0.312
SSDP24/20B	20	0.833	0.916	0.625	0.3125	0.625	0.312
SSDP24/24B	24	1	1.083	0.625	0.3125	0.625	0.312
SSDP24/25B	25	1.042	1.125	0.625	0.3125	0.625	0.312
SSDP24/30B	30	1.250	1.333	0.750	0.375	0.75	0.312
SSDP24/35B	35	1.458	1.541	0.750	0.375	0.75	0.312
SSDP24/40B	40	1.667	1.750	0.750	0.375	0.75	0.312
SSDP24/45B	45	1.875	1.958	0.750	0.375	0.75	0.312
SSDP24/48B	48	2	2.083	0.750	0.375	0.75	0.312
SSDP24/50B	50	2.083	2.166	0.750	0.375	0.75	0.312
SSDP24/55B	55	2.292	2.375	0.750	0.375	0.75	0.312
SSDP24/60B	60	2.500	2.583	1	0.5	0.812	0.312
SSDP24/63B	63	2.625	2.708	1	0.5	0.812	0.312
SSDP24/65B	65	2.708	2.791	1	0.5	0.812	0.312
SSDP24/70B	70	2.917	3	1	0.5	0.812	0.312
SSDP24/75B	75	3.125	3.208	1	0.5	0.812	0.312
SSDP24/80B	80	3.333	3.416	1	0.5	0.812	0.312
SSDP24/85B	85	3.542	3.625	1.250	0.5	0.937	0.312
SSDP24/90B	90	3.750	3.833	1.250	0.5	0.937	0.312
SSDP24/95B	95	3.958	4.041	1.250	0.5	0.937	0.312
SSDP24/96B	96	4	4.083	1.250	0.5	0.937	0.312
SSDP24/100B	100	4.167	4.250	1.250	0.5	0.937	0.312
SSDP24/120B	120	5	5.083	1.250	0.5	0.937	0.312

Please note: All dimensions subject to change. If a dimension is critical to your application please contact our Sales Department for confirmation.
For special or reworked gears please contact our Manufacturing Department for a quotation.