

CONTRAKOR A 100

Special anti-corrosion concentrate



Benefits for your application

- Anticorrosion agent with long-term effect
- Solvent-free concentrate
- Protects bright surfaces against corrosion
- Can be diluted with solvent
- Easy application
- Can be removed easily

Description

CONTRAKOR A 100 is a non-water-miscible anticorrosion concentrate based on mineral oil for bright and unprotected steel and iron surfaces.

Application

CONTRAKOR A 100 protects steel or iron parts against corrosion when stored outside or roofed.

If necessary, CONTRAKOR A100 can be diluted with white spirit and thin-bodied mineral oils.

If solvent is added, the product forms a very smooth, non-tacky film after evaporation of the solvent.

The mixing ratio depends on the corrosion protection requirements.

Application notes

CONTRAKOR A 100 is stirred at room temperature into the oil or solvent to be mixed and applied by injection or immersion onto steel or iron parts.

Full corrosion protection is only achieved after complete evaporation of the solvent.

Parts can be cleaned or degreased using a white spirit.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	CONTRAKOR A 100
Canister 20 l	+

Product data	CONTRAKOR A 100
Article number	047115
Chemical composition, type of oil	mineral oil
Lower service temperature	-10 °C / 14 °F
Upper service temperature	80 °C / 176 °F
Colour space	brown
Texture	viscous
Density, DIN 51757, 20 °C	approx. 0.94 g/cm ³
Kinematic viscosity, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 50 °C	approx. 480 mm ² /s
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	60 months



CONTRAKOR A 100

Special anti-corrosion concentrate



Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

**Klüber Lubrication München SE & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.**

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.