

Klüberfood NH1 C 6-150

Synthetic oil for chains in can lacquering lines for the food-processing industry



Benefits for your application

- A contributor towards cleaner chains resulting from low residue formation
- NSF H1 supporting process reliability
- Good wear protection as demonstrated from customer trials where we increased chain life more than 3 times. Potential extension in chain life subject to application.
- ISO 21469 certified - supports the compliance with the hygienic requirements in your production plant. You will find further information on ISO Standard 21469 on our website www.klueber.com

Description

Klüberfood NH1 C 6-150 is a special synthetic high-temperature oil on a polyglycol base developed for the lubrication of chains operating through can and tin-plate curing, lacquering and decorating ovens. Its formulation incorporating a special additive package enables significant friction reduction and good protection against wear and fretting corrosion particularly in the highly stressed pin / bush areas.

Klüberfood NH1 C 6-150 has a good viscosity-temperature behaviour resulting in lowest oil losses and good wear protection when permanently exposed to high temperature influences.

Klüberfood NH1 C 6-150 is NSF H1 registered and therefore complies with FDA 21 CFR § 178.3570. The lubricant was developed for incidental contact with products and packaging materials in the food-processing, cosmetics, pharmaceutical or animal feed industries. The use of Klüberfood NH1 C 6-150 can contribute to increase reliability of your production processes. We nevertheless recommend conducting an additional risk analysis, e.g. HACCP.

Application notes

Klüberfood NH1 C 6-150 may be applied via suitable chain lubrication system. Compatibility of the lubricant with the materials of the reservoir should be checked.

To attain the highest performance in curing and lacquering applications please do not hesitate to consult your local Klüber representative.

Mixing of Klüberfood NH1 C 6-150 oil with other incompatible or non-food-grade lubricants should be avoided!

For object/chain temperatures up to approx. 160 °C as may result from oven temperatures of approx. 300 °C under certain operating conditions. We recommend sufficient air removal under such conditions.

Initial lubrication

For best wear protection during the crucial running-in phase we recommend initial lubrication of the chain with Klüberfood NH1 C 6-150 or, alternatively, new chains may be lubricated with a special high- viscosity "primary running in lubricant" based on polyglycol via hot dipping (subject to the chain OEM, further details available on request).

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	Klüberfood NH1 C 6-150
Canister 20 l	+
Drum 200 l	+

Product data	Klüberfood NH1 C 6-150
Article number	002089
NSF-H1 registration	133 720
Colour space	yellow



Klüberfood NH1 C 6-150

Synthetic oil for chains in can lacquering lines for the food-processing industry

Product data	Klüberfood NH1 C 6-150
ISO viscosity grade, DIN ISO 3448	150
Viscosity index, DIN ISO 2909	>= 210
Kinematic viscosity, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 40 °C	approx. 150 mm ² /s
Kinematic viscosity, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 100 °C	approx. 28.5 mm ² /s
Pour point, DIN ISO 3016	<= -35 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

**Klüber Lubrication München SE & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.**

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.