

Klübersynth BZ 44-4000

Anticorrosion fluid with lubricating effect for rolling bearings



Benefits for your application

- **Less maintenance during operation**
due to the prevention of premature component failure enabled by very good anticorrosion and antiwear effect
- **Improved component performance**
due to the very good protection against False Brinelling, especially in rolling bearings performing oscillating and/or rotating movements

Description

Klübersynth BZ 44-4000 is a novel anticorrosion fluid based on a synthetic hydrocarbon oil with added lithium soap. Klübersynth BZ 44-4000 was developed as a supplementary product optimising the effect of greases in rolling bearings performing frequent oscillating and/or rotating movements. The innovative formulation of this product offers a unique double benefit: As a preservation fluid, Klübersynth BZ 44-4000 protects steel bearings against corrosion during storage. Furthermore, the additives it contains enhance the performance of the greases applied when the bearing is in use. Internal tests showed that in rolling bearings to which Klübersynth BZ 44-4000 had been applied grease lives were attained that were three times longer than those reached in untreated components. Fretting wear tests confirmed the product's preventive effect against False Brinelling damage.

Application

Klübersynth BZ 44-4000 is easy to apply and may be used as an alternative to conventional anticorrosion oil and as a primer for subsequent greasing. Typical applications include the long-

term and for-life lubrication of rolling bearings e.g. in wind turbines, electric motors, fans, automotive components or pumps.

Application notes

Klübersynth BZ 44-4000 can be applied by immersion, spraying or brush. Shake or stir product before use. Parts can be cleaned using a commercial cleansing agent. Due to its composition, Klübersynth BZ 44-4000 can be combined with the commonly used grease types. We recommend checking the miscibility of the grease in contact with the anticorrosion fluid, especially prior to series application.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

| Pack sizes | Klübersynth BZ 44-4000 |
|-------------|------------------------|
| Bucket 25 l | + |
| Drum 200 l | + |

| Product data | Klübersynth BZ 44-4000 |
|-----------------------------------|---------------------------|
| Article number | 047076 |
| Chemical composition, thickener | lithium soap |
| Chemical composition, type of oil | synthetic hydrocarbon oil |
| Lower service temperature | -40 °C / -40 °F |
| Upper service temperature | 140 °C / 284 °F |
| Colour space | beige |
| Appearance | milky |



Klübersynth BZ 44-4000

Anticorrosion fluid with lubricating effect for rolling bearings

| Product data | Klübersynth BZ 44-4000 |
|--|--------------------------------|
| Density, DIN 51757, 20 °C | approx. 0.84 g/cm ³ |
| Dynamic viscosity, DIN 53015, Höppler, 20°C | approx. 275 mPas |
| Anticorrosive properties on steel, DIN ISO 7120, method A, steel, 24 h/60 °C | no rust corrosion degree |
| Pour point of the base oil, DIN ISO 3016 | <= -40 °C |
| Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx. | 24 months |

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

**Klüber Lubrication München SE & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.**

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.