

Klübertemp YV 93-302

Sliding agent for valves, fittings and installations carrying oxygen up to medium partial pressure



Benefits for your application

- **High operational reliability for installations and components used with gaseous oxygen due to**
 - medium oxygen pressure surge resistance (see product data)
 - compatibility with most materials used in this industry
 - a wide service temperature range
- **Each product batch is checked for its reactivity to oxygen**

Description

Klübertemp YV 93-302 is a white sliding agent with good wetting ability based on perfluorinated polyether, solid lubricants and PTFE.

It offers medium oxygen pressure surge resistance and high resistance to a wide range of chemicals. To ensure continuous adherence to this high quality standard, Klübertemp YV 93-302 is manufactured in small series subject to strict hygiene requirements and each batch is inspected based on M 034-1 list of nonmetallic materials (213-075).

Application

Klübertemp YV 93-302 is a tried-and-tested sliding agent for all friction points with low to medium requirements and in combination with all materials used in gaseous oxygen installations.

The wide service temperature range underlines the universal application possibilities of this sliding agent. We recommend users conduct their tests using the complete component under conditions similar to series application.

The product's high pressure-absorption capacity and consistent friction values over a wide temperature range ensure constant actuation forces.

Test results show the product's usability for an O₂ content > 21 % by vol. under the operating conditions specified in the product data section of this product information leaflet.

Possible applications are:

- Oxygen valves
- Peripheral aggregates of chemical installations
- Hose couplings, e.g. oxygen pipe connections, sliding and plain bearings, bolts, slideways, etc.
- Steel and heavy industry
- Assembly aid for most rubber-elastic materials and plastics
- For the industrial handling, maintenance and care of oxygen components

Behaviour towards metals, elastomers and plastics

Klübertemp YV 93-302 is normally neutral towards metallic materials, plastics and elastomers within the given temperature range. Nevertheless, we recommend checking the compatibility of the sliding agent with materials in contact prior to its introduction.

Application notes

All surfaces to be wetted must be thoroughly cleaned prior to product application.

The friction / lubrication points of surfaces / components must be clean and bright (i.e. free from oil, grease, dirt particles or perspiration). We recommend cleaning the surfaces with clean white spirit and then Klüberalfa XZ 3-1, ensuring residue-free surfaces when dried. For valves and installations carrying oxygen, the application procedure must also be "oxygen clean" in order to attain a "ready for oxygen service" condition.

*Notes on the lower service temperature limit (see product data):

The service temperature is defined on the basis of physical and mechanical-dynamic product characteristics. If the product is intended to be used below the lower service temperature limit, it has to be checked if reliable operation of the component is ensured under these conditions. In cases of doubt, application-specific tests would have to be performed.

**Notes on the upper service temperature limit (see product data):

The service temperature is defined on the basis of physical and mechanical-dynamic product characteristics. When working in an atmosphere with added oxygen and/or under high oxygen partial pressure, the upper service temperature limit may be reduced due to a reaction with oxygen. To assess whether use in a particular application is safe, please refer to the product data section in this product information leaflet. In cases of doubt, application-specific tests would have to be performed.

Klübertemp YV 93-302

Sliding agent for valves, fittings and installations carrying oxygen up to medium partial pressure

Safety advice:

The resistance to oxygen was determined with the unused, contamination-free product. If the product is decomposed during use due to physical (temperature, electric discharge, pressure surges) or chemical influence or contaminated by foreign substances (e.g. easily oxidisable organic or inorganic materials, particularly iron metals, magnesium, aluminium, titanium or their alloys, e.g. rubbed-off particles, contamination from the environment), decomposition products or foreign substances can be generated which clearly reduce oxygen resistance. Furthermore, operating conditions have a major impact on the lubricant's behaviour in the application.

Therefore, it can be necessary or prescribed to conduct own safety-relevant examinations on the equipment or lubricated component.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	Klübertemp YV 93-302
Bottle 200 g	+
Can 1 kg	+



Product data	Klübertemp YV 93-302
Article number	013063
Chemical composition, type of oil	PFPE
Chemical composition	solid lubricant
Lower service temperature *	-60 °C
Upper service temperature **	200 °C
Colour space	white
Texture	homogeneous
Density at 20 °C	approx. 2.00 g/cm ³
Worked penetration, DIN ISO 2137, 25 °C, lower limit value	265 x 0.1 mm
Worked penetration, DIN ISO 2137, 25 °C, upper limit value	295 x 0.1 mm
Shear viscosity at 25 °C, shear rate 300 s ⁻¹ ; equipment:rotational viscometer	approx. 7 500 mPas
Copper corrosion, DIN 51811, (lubricating grease), 24h/100°C	1 - 100 corrosion degree
Flow pressure of lubricating greases, DIN 51805, test temperature: -60 °C	<= 1 400 mbar
Upper oxygen pressure limit up to a maximum operating temperature of 60 °C, reactivity when exposed to oxygen pressure surges, adiabatic procedure	100 bar
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	60 months



Klübertemp YV 93-302

Sliding agent for valves, fittings and installations carrying oxygen up to medium partial pressure



Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

**Klüber Lubrication München SE & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.**

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.